REDVET - Revista electrónica de Veterinaria - ISSN 1695-7504
Vol 25, No.1 (2024)
http://www.veterinaria.org
Received: 24.09.2024 Revised: 28.11.2024 Accepted: 13.12.2024

Image-Based Morphological Analysis and Time-Series Monitoring of Rice: A Review of Image Processing, Machine Learning and Emerging Approaches

Ramkishore Kushwaha[1] , Dr Saurabh Mandloi[2]

[1]PhD Scholar, School of computer Science, SAM Global University, Raisen (M.P.), INDIA, email id- ramkishor723623@gmail.com
[2]Associate Professor , School of computer Science, SAM Global University, Raisen (M.P.), INDIA saurabhm.research@gmail.com

ABSTRACT
Rice is one of the world's most important food crops, and accurate assessment of its morphological characteristics is essential for crop improvement, grain-quality evaluation, and yield estimation. Conventional measurement techniques are time-consuming, labor-intensive, and susceptible to human error. Recent advances in computer vision, machine learning, deep learning, and Internet of Things (IoT) technologies have enabled automated and non-destructive rice phenotyping. Early image-processing methods used thresholding, edge detection, contour extraction, and morphological operations to measure grain length, width, area, perimeter, and shape. More recent approaches employ convolutional neural networks (CNNs), U-Net segmentation, object detection, and high-throughput imaging platforms for automated characterization of rice grains, panicles, and plants. Smartphone-based imaging has also demonstrated the potential for affordable rice-quality assessment. However, most grain-level studies focus on static or post-harvest images, while comparatively limited research addresses repeated non-destructive imaging and quantitative modeling of individual grain development. This review examines the evolution of image-based rice analysis, compares conventional and AI-based techniques, identifies existing research gaps, and proposes an integrated framework incorporating image acquisition, preprocessing, segmentation, morphological feature extraction, temporal tracking, and growth modeling. The proposed framework provides a foundation for developing intelligent, cost-effective, and non-destructive rice phenotyping systems.

Keywords: Rice, computer vision, image processing, morphological analysis, grain phenotyping, deep learning, U-Net, time-series monitoring, growth modeling.

Introduction

Rice is a major cereal crop that plays a vital role in global food security. Its productivity and quality depend on genetic characteristics, environmental conditions, and crop-management practices. Consequently, accurate measurement of morphological traits is important for rice breeding, varietal identification, grain-quality assessment, and yield prediction [1,2].

Traditional rice phenotyping relies on manual measurement, visual observation, and laboratory analysis. Although these techniques provide useful information, they require considerable time and labor and may introduce observer-dependent errors. Measurements taken at isolated time points also provide limited information about the dynamic development of grains and plants.

Computer vision offers an efficient alternative by converting digital images into quantitative morphological information. Conventional image-processing techniques, including thresholding, edge detection, contour extraction, and connected-component analysis, have been used to estimate grain length, width, area, perimeter, and shape. Machine-learning and deep-learning techniques have subsequently improved the potential for automated classification, segmentation, and trait prediction [3].

Smartphone-based imaging combined with artificial neural networks has demonstrated the feasibility of low-cost rice characterization. Similarly, high-throughput phenotyping platforms have enabled repeated assessment of rice plants, panicles, and grains throughout the growing period. These developments indicate a transition from static image analysis toward dynamic phenotyping [4].

Despite this progress, repeated non-destructive monitoring of individual developing rice grains remains an important research opportunity. This paper reviews the major technological developments in image-based rice analysis and proposes an integrated framework for temporal morphological monitoring and growth prediction [5].

2. Review of Image-Based Rice Analysis

2.1 Conventional Image Processing and Feature Extraction

Early image-based rice analysis primarily employed thresholding, edge detection, and morphological operations to separate grains from the background. Techniques such as Otsu thresholding, adaptive thresholding, and Canny edge

REDVET - Revista electrónica de Veterinaria - ISSN 1695-7504
Vol 25, No.1 (2024)
http://www.veterinaria.org
Received: 24.09.2024 Revised: 28.11.2024 Accepted: 13.12.2024

detection are useful for identifying object boundaries under controlled imaging conditions. Connected-component analysis can subsequently separate individual objects for measurement [6].

After segmentation, morphological characteristics such as length, width, area, perimeter, aspect ratio, circularity, equivalent diameter, and major and minor axes can be calculated. Color and texture features may also support grain-quality assessment and variety classification [7].

However, conventional approaches are sensitive to illumination changes, background similarity, overlapping grains, and variations in object orientation. Their performance may therefore decrease when applied to complex images or field conditions.

2.2 Machine Learning and Deep Learning

Machine-learning algorithms, including support vector machines, artificial neural networks, and regression models, can use extracted morphological and color features to classify rice varieties and predict quality-related characteristics[8].

Deep learning has expanded these capabilities by learning complex visual representations directly from images. Convolutional neural networks support image classification and object detection, while semantic and instance segmentation models enable more detailed identification of grain boundaries and individual objects. U-Net is particularly relevant because its encoder-decoder architecture supports pixel-level segmentation [9].

A smartphone-based study by Aznan et al. demonstrated the potential of combining image-derived morpho-colorimetric characteristics with an artificial neural network for classifying commercial rice samples. The reported classification accuracy was approximately 90.7%, highlighting the potential of affordable imaging systems [10].

Deep-learning approaches nevertheless require representative training datasets, accurate annotations, computational resources, and independent validation. Their generalizability can be limited when lighting conditions, camera settings, backgrounds, or sample characteristics differ from those represented in the training data.

2.3 High-Throughput and Temporal Phenotyping

Recent research has expanded image-based analysis from individual grains to whole plants, panicles, and field-scale monitoring. Smartphone cameras, industrial imaging systems, unmanned aerial vehicles (UAVs), and automated phenotyping platforms enable large-scale data collection [11,12].

Tang et al. demonstrated the potential of image-based rice phenotyping across the growth period by extracting traits at plant, panicle, culm, and grain levels. Their work highlights the value of temporal phenotypic information for studying genotype–phenotype relationships and yield-related characteristics.

Similarly, research combining YOLOv5, ResNet50, and DeepSORT has demonstrated the potential of object detection and tracking for monitoring rice panicle development over successive observations. UAV-based CNN approaches have also been investigated for rice phenological-stage identification, demonstrating the applicability of deep learning to crop-scale monitoring [13].

These developments establish the importance of repeated imaging [14]. Nevertheless, monitoring individual developing grains presents additional challenges, including object overlap, changes in orientation, occlusion, and the need to maintain consistent object identities across images.




Figure 2.1: Block Diagram of Research Approach

3. Comparative Review and Research Gap

The principal methodological developments and their limitations are summarized in Table 1.

Table3.1: Comparison of image-based rice analysis approaches

Approach	Major techniques	Applications	Key limitations
Conventional image processing	Thresholding, edge detection, contour extraction	Grain size, area, perimeter, and shape	Sensitive to illumination and overlapping objects

Feature-based machine learning	ANN, SVM, regression	Variety classification and quality assessment	Depends on feature selection and dataset quality
Deep-learning segmentation	CNN, U-Net	Grain boundary detection and individual-object identification	Requires annotated data and computational resources
High-throughput phenotyping	Automated imaging, UAV, image-analysis pipelines	Plant growth, panicle traits, and crop monitoring	Equipment costs and environmental variability
Temporal tracking	Object detection, feature association, tracking algorithms	Developmental monitoring across successive images	Identity loss, occlusion, and inconsistent imaging
Growth modeling	Polynomial, logistic, Gompertz, and nonlinear regression	Growth-rate estimation and trait prediction	Requires reliable longitudinal measurements

The literature indicates three major research gaps. First, many rice-grain studies focus on static or post-harvest images, providing limited information about developmental changes. Second, temporal phenotyping has advanced more rapidly at plant, panicle, and field levels than at the individual developing-grain level. Third, variations in illumination, camera position, object orientation, and overlapping structures continue to challenge reliable segmentation and tracking.
Therefore, an integrated framework combining repeated image acquisition, robust segmentation, morphological feature extraction, individual-object tracking, and quantitative growth modeling is required. Such a framework would extend rice analysis from measuring final grain characteristics to understanding how those characteristics develop over time.

4. Proposed Framework and Methodology

The proposed framework integrates computer vision and temporal analysis into six stages.

- **Stage 1: Repeated Image Acquisition.** Rice grains or developing plant structures are photographed at predefined intervals using a fixed camera, controlled illumination, a consistent background, and a calibrated imaging distance. For developing grains, imaging must be performed without disrupting their natural growth.
- **Stage 2: Image Preprocessing.** Images are corrected for noise, illumination variation, contrast, and background interference. Standardization improves consistency between observations.
- **Stage 3: Segmentation and Object Identification.** Conventional thresholding and morphological operations can be used for simple images, whereas U-Net or related deep-learning models may be applied to complex backgrounds and overlapping structures. Individual objects are identified for subsequent tracking.
- **Stage 4: Morphological Feature Extraction.** The segmented objects are characterized using grain length, width, area, perimeter, aspect ratio, major and minor axes, circularity, and relevant color features. Pixel measurements are converted into physical units using an appropriate calibration reference.
- **Stage 5: Temporal Tracking.** Consistent identifiers are assigned to the same grain or plant structure across consecutive images. The resulting longitudinal dataset records each object's morphological characteristics at different observation times. Tracking accuracy must be evaluated because occlusion or changes in orientation can lead to identity errors.
- **Stage 6: Growth Modeling and Prediction.** Temporal measurements are used to estimate growth trajectories and predict future morphological characteristics. Polynomial, logistic, Gompertz, or other nonlinear regression models may be evaluated according to the observed developmental pattern.

5. Future Research Directions

Future studies should develop standardized datasets containing repeated images of the same rice samples throughout development. Such datasets would support the training and validation of segmentation, tracking, and growth-prediction models.

Integration with environmental sensors measuring temperature, humidity, soil moisture, light intensity, and nutrient conditions could help explain variation in morphological development. IoT-enabled cameras and edge-computing devices, such as Raspberry Pi systems, could facilitate automated image acquisition and data transmission.
Furthermore, CNN-LSTM architectures and temporal transformers could be investigated for learning spatial and temporal patterns jointly. Their effectiveness should be compared with conventional growth models using independent datasets. Particular attention should be given to measurement calibration, tracking reliability, computational efficiency, and performance under realistic growing conditions.

6. Conclusion

Image-based rice morphological analysis has progressed from conventional thresholding and edge detection to machine learning, deep-learning segmentation, high-throughput phenotyping, and temporal tracking. These technologies have improved the potential for automated measurement of grain characteristics, variety classification, quality assessment, and crop monitoring.
However, individual-grain-level temporal monitoring remains comparatively underdeveloped. An integrated system combining repeated image acquisition, preprocessing, segmentation, morphological feature extraction, temporal tracking, and growth modeling offers a promising direction for addressing this limitation. By generating longitudinal morphological datasets, the proposed framework can support non-destructive monitoring, growth-rate estimation, and prediction of final grain characteristics. Integration with deep learning and IoT technologies may further enable scalable and cost-effective rice phenotyping for research and agricultural decision-making.

References

1. Kuo, T.-Y., Chung, C.-L., Chen, S.-Y., Lin, H.-A., & Kuo, Y.-F. (2016). Identifying rice grains using image analysis and sparse-representation-based classification. Computers and Electronics in Agriculture, 127, 716–725. https://doi.org/10.1016/j.compag.2016.07.020
2. Boschetti, M., Busetto, L., Manfron, G., Laborte, A., Asilo, S., Pazhanivelan, S., & Nelson, A. (2017). PhenoRice: A method for automatic extraction of spatio-temporal information on rice crops using satellite data time series. Remote Sensing of Environment, 194, 347–365. https://doi.org/10.1016/j.rse.2017.03.029
3. Aznan, A., Gonzalez Viejo, C., Pang, A., & Fuentes, S. (2021). Computer vision and machine learning analysis of commercial rice grains: A potential digital approach for consumer perception studies. Sensors, 21(19), 6354. https://doi.org/10.3390/s21196354 DOI.org
4. Yang, Q., Shi, L., Han, J., Yu, J., & Huang, K. (2020). A near real-time deep learning approach for detecting rice phenology based on UAV images. Agricultural and Forest Meteorology, 287, 107938. https://doi.org/10.1016/j.agrformet.2020.107938 DOI.org
5. Image Processing Techniques for Diagnosing Rice Plant Disease: A Survey. (2020). Procedia Computer Science, 167, 516–530. https://doi.org/10.1016/j.procs.2020.03.308
6. Manavalan, R. (2020). Automatic identification of diseases in grains crops through computational approaches: A review. Computers and Electronics in Agriculture, 105802. https://doi.org/10.1016/j.compag.2020.105802 DOI.org
7. Convolutional Neural Networks in Computer Vision for Grain Crop Phenotyping: A Review. (2022). Agronomy, 12(11), 2659. https://doi.org/10.3390/agronomy12112659
8. A VI-based phenology adaptation approach for rice crop monitoring using UAV multispectral images. (2022). Field Crops Research, 277, 108419. https://doi.org/10.1016/j.fcr.2021.108419
9. Tang, Z., Chen, Z., Gao, Y., Xue, R., Geng, Z., Bu, Q., Wang, Y., Chen, X., Jiang, Y., Chen, F., Yang, W., Hu, W., et al. (2023). A strategy for the acquisition and analysis of image-based phenome in rice during the whole growth period. Plant Phenomics, 5, 0058. https://doi.org/10.34133/plantphenomics.0058
10. Zhou, Q., Guo, W., Chen, N., Wang, Z., Li, G., Ding, Y., Ninomiya, S., Mu, Y., et al. (2023). Analyzing nitrogen effects on rice panicle development by panicle detection and time-series tracking. Plant Phenomics, 5, 0048. https://doi.org/10.34133/plantphenomics.0048
11. Lei, L., Yang, Q., Yang, L., Shen, T., Wang, R., et al. (2024). Deep learning implementation of image segmentation in agricultural applications: A comprehensive review. Artificial Intelligence Review, 57, 149. https://doi.org/10.1007/s10462-024-10775-6
12. Murphy, K. M., Ludwig, E., Gutierrez, J., & Gehan, M. A. (2024). Deep learning in image-based plant phenotyping. Annual Review of Plant Biology, 75, 771–795. https://doi.org/10.1146/annurev-arplant-070523-042828 DOI.org
13. Sun, J., Jia, H., Ren, Z., Cui, J., Yang, W., & Song, P. (2024). Accurate rice grain counting in natural morphology: A method based on image classification and object detection. Computers and Electronics in Agriculture. https://doi.org/10.1016/j.compag.2024.109490 DOI.org
14. Predicting rice diseases using advanced technologies at different scales: Present status and future perspectives. (2023). aBIOTECH, 4, 359–371. https://doi.org/10.1007/s42994-023-00126-4